

SECURITY UNITS

- **Safe Storage:** Protects valuable materials and sensitive items from loss or pilferage.
- **Ready View of Contents:** Heavy-gauge open wire construction keeps the entire contents of the truck visible at all times, making it easy to check inventory.
- **Durable chrome finish** will not chip or flake.
- **Modular offering:** Build stationary or mobile security units with existing shelf, post, and caster options.
- **Ergonomic, 1/4-Turn Door Handle:** Makes opening and closing the unit easier than conventional security unit designs.
- **Double Door:** Each door opens 270 degrees and can be secured along the sides of the unit.
- **Time Saving Assembly:** Security units assemble quickly — right out of the box.
- **Shipped Knocked-Down:** Saves on freight costs. Easily assembled.



Handle (open position)



Handle (closed position)

OLYMPIC

STORAGE COMPANY

Reliable space . . . economically.

Specifications

Please note: All component parts below must be purchased separately. Security Cart component parts will change based on size and choice of security unit.

Mobile:

Security Cage	Quantity: 1
Shelves	Quantity: 2-4
Mobile Posts	Quantity: 4
Stem Casters	Quantity: 4

Stationary:

Security Cart Cage	Quantity: 1
Shelves	Quantity: 2-4
Stationary Posts	Quantity: 4

Olympic Security Enclosure Kit

Model No. Chrome	For Use With Shelves (Width x Length)		Approx. Pkd. Wt.	
	(in.)	(mm)	(lbs.)	(kg)
JSEC53-CTN	24x36	610x914	110	50
JSEC55-CTN	24x48	610x1219	125	57
JSEC56-CTN	24x60	610x1524	135	59

Shelves

Model No. Chrome	Nominal Size (Width x Length)		Approx. Pkd. Wt.	
	(in.)	(mm)	(lbs.)	(kg)
J2436C	24x36	610x914	13	5.9
J2448C	24x48	610x1219	16	7.3
J2460C	24x60	610x1524	21	9.5

Posts (Mobile and Stationary)

Stationary posts are equipped with a leveling bolt to account for uneven floors. Mobile Post are for use with Stem Casters on Mobile Security Units. Security cages are sized to work specifically with these posts.

Model No. Chrome	Post Type	Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
J65C	Stationary	65 ³ / ₄	1670	4 ¹ / ₄	2
J63UC	Mobile	61 ¹³ / ₁₆	1570	3 ¹ / ₂	1.6

Stem Casters

Model No. Chrome	Caster Type	Wheel Diameter		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
J5	Stem/Swivel	5	127	1 ¹ / ₄	32	Resilient	200	90	2 ¹ / ₂	1.1
J5B	Stem/Brake	5	127	1 ¹ / ₄	32	Resilient	200	90	2 ⁵ / ₈	1.2

Actual Dimensions — Mobile Unit

The dimensions below assume the unit is fully assembled with top/bottom shelves, four posts, 5" (127mm) diameter casters, and Security Enclosures.

Nominal Width x Length		Actual Width		Actual Length		Actual Height	
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)
24x36	610x914	29 ¹¹ / ₁₆	754	40 ³ / ₄	1035	68 ¹ / ₂	1740
24x48	610x1219	29 ¹¹ / ₁₆	754	52 ³ / ₄	1340	68 ¹ / ₂	1740
24x60	610x1524	29 ¹¹ / ₁₆	754	64 ³ / ₄	1645	68 ¹ / ₂	1740

Actual Dimensions — Stationary Unit

The dimensions below assume the unit is fully assembled with top/bottom shelves, four posts, and Security Enclosures.

Nominal Width x Length		Actual Width		Actual Length		Actual Height	
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)
24x36	610x914	27 ¹ / ₄	692	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695
24x48	610x1219	27 ¹ / ₄	692	50 ¹ / ₂	1295	66 ¹³ / ₁₆	1695
24x60	610x1524	27 ¹ / ₄	692	62 ¹ / ₂	1587	66 ¹³ / ₁₆	1695